

Continuous Systems, Infinite Degrees of Freedom

Giacomo Boffi

Dipartimento di Ingegneria Civile e Ambientale, Politecnico di Milano

June 23, 2014

Continuous Systems

Beams in Flexure

Equation of motion

Earthquake Loading

Free Vibrations

Eigenpairs of a Uniform Beam

Simply Supported Beam

Cantilever Beam

Mode Orthogonality

Forced Response

Earthquake Response

Example

Discrete models

Until now, structures were discretized, maybe lumping their masses in the *dynamical degrees of freedom* or maybe to use the *FEM* to derive a stiffness matrix, to be subjected to static condensation in the occurrence of lumped masses or, on the contrary, to be used *as is*. Multistory buildings are excellent examples of structures for which a few dynamical degrees of freedom can describe the dynamical response.

Continuous models

For different type of structures (e.g., bridges, chimneys), a lumped mass model is not the first option. While a *FE* model is always appropriate, there is no apparent way of lumping the structural masses in a way that is obviously correct, and a great number of degrees of freedom must be retained in the dynamic analysis.




An alternative to detailed *FE* models is deriving the equation of motion, in terms of partial derivatives differential equation, for the continuous systems.

There are many different continuous systems whose dynamics are approachable with the instruments of classical mechanics,

- ▶ taught strings,
- ▶ axially loaded rods,
- ▶ beams in flexure,
- ▶ plates and shells,
- ▶ 3D solids.

In the following, we will focus our interest on beams in flexure.

EoM for an undamped beam




$$df_i = m dx \frac{\partial^2 u}{\partial t^2}$$

At the left, a straight beam with characteristic depending on position x : $m = m(x)$ and $EJ = EJ(x)$; with the signs conventions for displacements, accelerations, forces and bending moments reported left, the equation of vertical equilibrium for an infinitesimal slice of beam is

$$V - (V + \frac{\partial V}{\partial x} dx) + m dx \frac{\partial^2 u}{\partial t^2} - p(x, t) dx = 0.$$

EoM for an undamped beam




At the left, a straight beam with characteristic depending on position x : $m = m(x)$ and $EJ = EJ(x)$; with the signs conventions for displacements, accelerations, forces and bending moments reported left, the equation of vertical equilibrium for an infinitesimal slice of beam is

$$V - (V + \frac{\partial V}{\partial x} dx) + m dx \frac{\partial^2 u}{\partial t^2} - p(x, t) dx = 0.$$

Rearranging and simplifying dx ,

$$\frac{\partial V}{\partial x} = m \frac{\partial^2 u}{\partial t^2} - p(x, t).$$

EoM for an undamped beam



At the left, a straight beam with characteristic depending on position x : $m = m(x)$ and $EJ = EJ(x)$; with the signs conventions for displacements, accelerations, forces and bending moments reported left, the equation of vertical equilibrium for an infinitesimal slice of beam is

$$V - (V + \frac{\partial V}{\partial x} dx) + m dx \frac{\partial^2 u}{\partial t^2} - p(x, t) dx = 0.$$

Rearranging and simplifying dx ,

$$\frac{\partial V}{\partial x} = m \frac{\partial^2 u}{\partial t^2} - p(x, t).$$

The rotational equilibrium, neglecting rotational inertia and infinitesimals of higher order, simplifying dx is

$$\frac{\partial M}{\partial x} = V.$$

Equation of motion, 2

Deriving with respect to x both members of the rotational equilibrium equation, it is

$$\frac{\partial V}{\partial x} = \frac{\partial^2 M}{\partial x^2}$$

Equation of motion, 2

Deriving with respect to x both members of the rotational equilibrium equation, it is

$$\frac{\partial V}{\partial x} = \frac{\partial^2 M}{\partial x^2}$$

Substituting in the equation of vertical equilibrium and rearranging

$$m(x) \frac{\partial^2 u}{\partial t^2} - \frac{\partial^2 M}{\partial x^2} = p(x, t)$$

Equation of motion, 2

Deriving with respect to x both members of the rotational equilibrium equation, it is

$$\frac{\partial V}{\partial x} = \frac{\partial^2 M}{\partial x^2}$$

Substituting in the equation of vertical equilibrium and rearranging

$$m(x) \frac{\partial^2 u}{\partial t^2} - \frac{\partial^2 M}{\partial x^2} = p(x, t)$$

Using the moment-curvature relationship,

$$M = -EJ \frac{\partial^2 u}{\partial x^2}$$

Equation of motion, 2

Deriving with respect to x both members of the rotational equilibrium equation, it is

$$\frac{\partial V}{\partial x} = \frac{\partial^2 M}{\partial x^2}$$

Substituting in the equation of vertical equilibrium and rearranging

$$m(x) \frac{\partial^2 u}{\partial t^2} - \frac{\partial^2 M}{\partial x^2} = p(x, t)$$

Using the moment-curvature relationship,

$$M = -EJ \frac{\partial^2 u}{\partial x^2}$$

and substituting in the equation above we have the equation of dynamic equilibrium

$$m(x) \frac{\partial^2 u}{\partial t^2} + \frac{\partial^2}{\partial x^2} \left[EJ(x) \frac{\partial^2 u}{\partial x^2} \right] = p(x, t).$$

Effective Earthquake Loading

If our continuous structure is subjected to earthquake excitation, we will write, as usual, $u_{\text{tot}} = u(x, t) + u_g(t)$ and, consequently,

$$\ddot{u}_{\text{tot}} = \ddot{u}(x, t) + \ddot{u}_g(t)$$

and, using the usual considerations,

$$p_{\text{eff}}(x, t) = -m(x)\ddot{u}_g(t).$$

Continuous
Systems, Infinite
Degrees of
Freedom

Giacomo Boffi

Continuous
Systems

Beams in Flexure

Equation of motion

Earthquake Loading

Free Vibrations

Eigenpairs of a Uniform
Beam

Simply Supported Beam

Cantilever Beam

Mode Orthogonality

Forced Response

Earthquake Response

Example

Effective Earthquake Loading

Continuous
Systems, Infinite
Degrees of
Freedom

Giacomo Boffi

If our continuous structure is subjected to earthquake excitation, we will write, as usual, $u_{\text{tot}} = u(x, t) + u_g(t)$ and, consequently,

$$\ddot{u}_{\text{tot}} = \ddot{u}(x, t) + \ddot{u}_g(t)$$

and, using the usual considerations,

$$p_{\text{eff}}(x, t) = -m(x)\ddot{u}_g(t).$$

In p_{eff} we have a separation of variables: in the case of earthquake excitation all the considerations we have done on expressing the response in terms of static modal responses and dynamic pseudo acceleration response will be applicable.

Continuous
Systems

Beams in Flexure

Equation of motion

Earthquake Loading

Free Vibrations

Eigenpairs of a Uniform
Beam

Simply Supported Beam

Cantilever Beam

Mode Orthogonality

Forced Response

Earthquake Response

Example

Effective Earthquake Loading

Continuous
Systems, Infinite
Degrees of
Freedom

Giacomo Boffi

If our continuous structure is subjected to earthquake excitation, we will write, as usual, $u_{\text{tot}} = u(x, t) + u_g(t)$ and, consequently,

$$\ddot{u}_{\text{tot}} = \ddot{u}(x, t) + \ddot{u}_g(t)$$

and, using the usual considerations,

$$p_{\text{eff}}(x, t) = -m(x)\ddot{u}_g(t).$$

In p_{eff} we have a separation of variables: in the case of earthquake excitation all the considerations we have done on expressing the response in terms of static modal responses and dynamic pseudo acceleration response will be applicable.

Only a word of caution, in every case we must consider the component of earthquake acceleration *parallel* to the transverse motion of the beam.

Continuous
Systems

Beams in Flexure

Equation of motion

Earthquake Loading

Free Vibrations

Eigenpairs of a Uniform
Beam

Simply Supported Beam

Cantilever Beam

Mode Orthogonality

Forced Response

Earthquake Response

Example

For free vibrations, $p(x, t) \equiv 0$ and the equation of equilibrium is

$$m(x) \frac{\partial^2 u}{\partial t^2} + \frac{\partial^2}{\partial x^2} \left[EJ(x) \frac{\partial^2 u}{\partial x^2} \right] = 0.$$

Using separation of variables, $u(x, t) = q(t)\phi(x)$ with the following notations for the partial derivatives,

$$\frac{\partial u}{\partial t} = \dot{q}\phi, \quad \frac{\partial u}{\partial x} = q\phi'$$

etc for higher order derivatives, we have

$$m(x)\ddot{q}(t)\phi(x) + q(x) [EJ(x)\phi'']'' = 0.$$

Dividing both terms in

$$m(x)\ddot{q}(t)\phi(x) + q(t) [EJ(x)\phi''(x)]'' = 0.$$

by $m(x)u(x, t) = m(x)q(t)\phi(x)$ and rearranging, we have

$$-\frac{\ddot{q}(t)}{q(t)} = \frac{[EJ(x)\phi''(x)]''}{m(x)\phi(x)}.$$

Continuous
Systems

Beams in Flexure

Equation of motion

Earthquake Loading

Free Vibrations

Eigenpairs of a Uniform
Beam

Simply Supported Beam

Cantilever Beam

Mode Orthogonality

Forced Response

Earthquake Response

Example

Dividing both terms in

$$m(x)\ddot{q}(t)\phi(x) + q(t) [EJ(x)\phi''(x)]'' = 0.$$

by $m(x)u(x, t) = m(x)q(t)\phi(x)$ and rearranging, we have

$$-\frac{\ddot{q}(t)}{q(t)} = \frac{[EJ(x)\phi''(x)]''}{m(x)\phi(x)}.$$

The left member is a function of time only, the right member a function of position only, and they are equal...

Continuous
Systems

Beams in Flexure

Equation of motion

Earthquake Loading

Free Vibrations

Eigenpairs of a Uniform
Beam

Simply Supported Beam

Cantilever Beam

Mode Orthogonality

Forced Response

Earthquake Response

Example

Dividing both terms in

$$m(x)\ddot{q}(t)\phi(x) + q(t) [EJ(x)\phi''(x)]'' = 0.$$

by $m(x)u(x, t) = m(x)q(t)\phi(x)$ and rearranging, we have

$$-\frac{\ddot{q}(t)}{q(t)} = \frac{[EJ(x)\phi''(x)]''}{m(x)\phi(x)}.$$

The left member is a function of time only, the right member a function of position only, and they are equal... this is possible if and only if both terms are constant, let's name this constant ω^2 and write

$$-\frac{\ddot{q}(t)}{q(t)} = \frac{[EJ(x)\phi''(x)]''}{m(x)\phi(x)} = \omega^2,$$

Continuous
Systems

Beams in Flexure

Equation of motion

Earthquake Loading

Free Vibrations

Eigenpairs of a Uniform
Beam

Simply Supported Beam

Cantilever Beam

Mode Orthogonality

Forced Response

Earthquake Response

Example

From the previous equations we can derive the following two

$$\ddot{q} + \omega^2 q = 0$$

$$[EJ(x)\phi''(x)]'' = \omega^2 m(x)\phi(x)$$

Continuous
Systems

Beams in Flexure

Equation of motion

Earthquake Loading

Free Vibrations

Eigenpairs of a Uniform
Beam

Simply Supported Beam

Cantilever Beam

Mode Orthogonality

Forced Response

Earthquake Response

Example

From the previous equations we can derive the following two

$$\ddot{q} + \omega^2 q = 0$$

$$[EJ(x)\phi''(x)]'' = \omega^2 m(x)\phi(x)$$

From the first, $\ddot{q} + \omega^2 q = 0$, it is apparent that free vibration shapes $\phi(x)$ will be modulated by a trig function

$$q(t) = A \sin \omega t + B \cos \omega t.$$

From the previous equations we can derive the following two

$$\ddot{q} + \omega^2 q = 0$$

$$[EJ(x)\phi''(x)]'' = \omega^2 m(x)\phi(x)$$

From the first, $\ddot{q} + \omega^2 q = 0$, it is apparent that free vibration shapes $\phi(x)$ will be modulated by a trig function

$$q(t) = A \sin \omega t + B \cos \omega t.$$

To find something about ω 's and ϕ 's (that is, the eigenvalues and the *eigenfunctions* of our problem), we have to introduce an important simplification.

Eigenpairs of a uniform beam

With $EJ = \text{const.}$ and $m = \text{const.}$, we have from the second equation in previous slide,

$$EJ\phi^{IV} - \omega^2 m\phi = 0,$$

with $\beta^4 = \frac{\omega^2 m}{EJ}$ it is

$$\phi^{IV} - \beta^4 \phi = 0$$

a differential equation of 4th order with constant coefficients.

Eigenpairs of a uniform beam

With $EJ = \text{const.}$ and $m = \text{const.}$, we have from the second equation in previous slide,

$$EJ\phi^{IV} - \omega^2 m\phi = 0,$$

with $\beta^4 = \frac{\omega^2 m}{EJ}$ it is

$$\phi^{IV} - \beta^4 \phi = 0$$

a differential equation of 4th order with constant coefficients.

Substituting $\phi = \exp st$ and simplifying,

$$s^4 - \beta^4 = 0,$$

the roots of the associated polynomial are

$$s_1 = \beta, s_2 = -\beta, s_3 = i\beta, s_4 = -i\beta$$

and the general integral is

$$\phi(x) = \mathcal{A} \sin \beta x + \mathcal{B} \cos \beta x + \mathcal{C} \sinh \beta x + \mathcal{D} \cosh \beta x$$

Constants of Integration

For a uniform beam in free vibration, the general integral is

$$\phi(x) = \mathcal{A} \sin \beta x + \mathcal{B} \cos \beta x + \mathcal{C} \sinh \beta x + \mathcal{D} \cosh \beta x$$

In this expression we see 5 parameters, the 4 constants of integration and the wave number β (further consideration shows that the constants can be arbitrarily scaled).

In general for the transverse motion of a segment of beam supported at the extremes we can write exactly 4 equations expressing boundary conditions, either from kinematic or static considerations.

Continuous Systems

Beams in Flexure

Equation of motion

Earthquake Loading

Free Vibrations

Eigenpairs of a Uniform
Beam

Simply Supported Beam

Cantilever Beam

Mode Orthogonality

Forced Response

Earthquake Response

Example

For a uniform beam in free vibration, the general integral is

$$\phi(x) = \mathcal{A} \sin \beta x + \mathcal{B} \cos \beta x + \mathcal{C} \sinh \beta x + \mathcal{D} \cosh \beta x$$

In this expression we see 5 parameters, the 4 constants of integration and the wave number β (further consideration shows that the constants can be arbitrarily scaled).

In general for the transverse motion of a segment of beam supported at the extremes we can write exactly 4 equations expressing boundary conditions, either from kinematic or static considerations.

All these boundary conditions

- ▶ lead to linear, homogeneous equation where
- ▶ the coefficients of the equations depend on the parameter β .

Imposing the boundary conditions give a homogeneous linear system with coefficients depending on β , hence:

- ▶ a non trivial solution is possible only for particular values of β , for which the determinant of the matrix of coefficients is equal to zero and
- ▶ the constants are known within a proportionality factor.

Continuous Systems

Beams in Flexure

Equation of motion

Earthquake Loading

Free Vibrations

Eigenpairs of a Uniform
Beam

Simply Supported Beam

Cantilever Beam

Mode Orthogonality

Forced Response

Earthquake Response

Example

Imposing the boundary conditions give a homogeneous linear system with coefficients depending on β , hence:

- ▶ a non trivial solution is possible only for particular values of β , for which the determinant of the matrix of coefficients is equal to zero and
- ▶ the constants are known within a proportionality factor.

In the case of *MDOF* systems, the determinantal equation is an algebraic equation of order N , giving exactly N eigenvalues, now the equation to be solved is a transcendental equation (examples from the next slide), with an infinity of solutions.

Continuous
Systems

Beams in Flexure

Equation of motion

Earthquake Loading

Free Vibrations

Eigenpairs of a Uniform
Beam

Simply Supported Beam

Cantilever Beam

Mode Orthogonality

Forced Response

Earthquake Response

Example

Simply supported beam

Consider a simply supported uniform beam of length L , displacements at both ends must be zero, as well as the bending moments:

$$\begin{aligned}\phi(0) = \mathcal{B} + \mathcal{D} &= 0, & \phi(L) &= 0, \\ -EJ\phi''(0) = \beta^2 EJ(\mathcal{B} - \mathcal{D}) &= 0, & -EJ\phi''(L) &= 0.\end{aligned}$$

The conditions for the left support require that $\mathcal{B} = \mathcal{D} = 0$

Simply supported beam

Consider a simply supported uniform beam of length L , displacements at both ends must be zero, as well as the bending moments:

$$\begin{aligned}\phi(0) = \mathcal{B} + \mathcal{D} &= 0, & \phi(L) &= 0, \\ -EJ\phi''(0) = \beta^2 EJ(\mathcal{B} - \mathcal{D}) &= 0, & -EJ\phi''(L) &= 0.\end{aligned}$$

The conditions for the left support require that $\mathcal{B} = \mathcal{D} = 0$
Now, we can write the equations for the right support as

$$\begin{aligned}\phi(L) = \mathcal{A} \sin \beta L + \mathcal{C} \sinh \beta L &= 0 \\ -EJ\phi''(L) = \beta^2 EJ(\mathcal{A} \sin \beta L - \mathcal{C} \sinh \beta L) &= 0\end{aligned}$$

or

$$\begin{bmatrix} + \sin \beta L & + \sinh \beta L \\ + \sin \beta L & - \sinh \beta L \end{bmatrix} \begin{Bmatrix} \mathcal{A} \\ \mathcal{C} \end{Bmatrix} = \begin{Bmatrix} 0 \\ 0 \end{Bmatrix}.$$

Simply supported beam, 2

For the simply supported beam we have

$$\begin{bmatrix} +\sin\beta L & +\sinh\beta L \\ +\sin\beta L & -\sinh\beta L \end{bmatrix} \begin{Bmatrix} \mathcal{A} \\ \mathcal{C} \end{Bmatrix} = \begin{Bmatrix} 0 \\ 0 \end{Bmatrix}.$$

The determinant is $-2\sin\beta L \sinh\beta L$, equating to zero with the understanding that $\sinh\beta L \neq 0$ if $\beta \neq 0$ results in

$$\sin\beta L = 0.$$

Simply supported beam, 2

For the simply supported beam we have

$$\begin{bmatrix} +\sin\beta L & +\sinh\beta L \\ +\sin\beta L & -\sinh\beta L \end{bmatrix} \begin{Bmatrix} \mathcal{A} \\ \mathcal{C} \end{Bmatrix} = \begin{Bmatrix} 0 \\ 0 \end{Bmatrix}.$$

The determinant is $-2\sin\beta L \sinh\beta L$, equating to zero with the understanding that $\sinh\beta L \neq 0$ if $\beta \neq 0$ results in

$$\sin\beta L = 0.$$

All positive β solutions are given by

$$\beta L = n\pi$$

with $n = 1, \dots, \infty$. We have an infinity of eigenvalues,

$$\beta_n = \frac{n\pi}{L} \text{ and } \omega_n = \beta^2 \sqrt{\frac{EJ}{m}} = n^2 \pi^2 \sqrt{\frac{EJ}{mL^4}}$$

and of eigenfunctions

$$\phi_1 = \sin \frac{\pi x}{L}, \quad \phi_2 = \sin \frac{2\pi x}{L}, \quad \phi_3 = \sin \frac{3\pi x}{L}, \quad \dots$$

For $x = 0$, we have zero displacement and zero rotation

$$\phi(0) = \mathcal{B} + \mathcal{D} = 0, \quad \phi'(0) = \beta(\mathcal{A} + \mathcal{C}) = 0,$$

for $x = L$, both bending moment and shear must be zero

$$-EJ\phi''(L) = 0, \quad -EJ\phi'''(L) = 0.$$

Substituting the expression of the general integral, with $\mathcal{D} = -\mathcal{B}$, $\mathcal{C} = -\mathcal{A}$ from the left end equations, in the right end equations and simplifying

$$\begin{bmatrix} \sinh \beta L + \sin \beta L & \cosh \beta L + \cos \beta L \\ \cosh \beta L + \cos \beta L & \sinh \beta L - \sin \beta L \end{bmatrix} \begin{Bmatrix} \mathcal{A} \\ \mathcal{B} \end{Bmatrix} = \begin{Bmatrix} 0 \\ 0 \end{Bmatrix}.$$

Cantilever beam, 2

Imposing a zero determinant results in

$$\begin{aligned} &(\cosh^2 \beta L - \sinh^2 \beta L) + \\ &+ (\sin^2 \beta L + \cos^2 \beta L) + 2 \cos \beta L \cosh \beta L = \\ &= 2(1 + \cos \beta L \cosh \beta L) = 0 \end{aligned}$$

Continuous Systems

Beams in Flexure

Equation of motion

Earthquake Loading

Free Vibrations

Eigenpairs of a Uniform
Beam

Simply Supported Beam

Cantilever Beam

Mode Orthogonality

Forced Response

Earthquake Response


Example

Cantilever beam, 2

Imposing a zero determinant results in

$$\begin{aligned} & (\cosh^2 \beta L - \sinh^2 \beta L) + \\ & + (\sin^2 \beta L + \cos^2 \beta L) + 2 \cos \beta L \cosh \beta L = \\ & = 2(1 + \cos \beta L \cosh \beta L) = 0 \end{aligned}$$

Rearranging, it is $\cos \beta L = -(\cosh \beta L)^{-1}$; plotting these functions on the same graph gives insight on the roots



it is $\beta_1 L = 1.8751$ and $\beta_2 L = 4.6941$, while for $n > 2$ a good approximation is $\beta_n L \approx \frac{2n-1}{2}\pi = n\pi - \frac{\pi}{2}$.

Cantilever beam, 3


Eigenfunctions are given by

$$\phi_n(x) = C_n \left[(\cosh \beta_n x - \cos \beta_n x) - \frac{\cosh \beta_n L + \cos \beta_n L}{\sinh \beta_n L + \sin \beta_n L} (\sinh \beta_n x - \sin \beta_n x) \right]$$

Continuous
Systems

Beams in Flexure

- Equation of motion
- Earthquake Loading
- Free Vibrations
- Eigenpairs of a Uniform Beam
 - Simply Supported Beam
 - Cantilever Beam**
- Mode Orthogonality
- Forced Response
- Earthquake Response
- Example



Above, in abscissas x/L and in ordinates $\phi_n(x)$ for the first 5 modes of vibration of the cantilever beam.

n	1	2	3	4	5
$\beta_n L$	1.8751	4.6941	7.8548	10.9962	$\approx 4.5\pi$
$\omega \sqrt{\frac{mL^4}{EJ}}$	3.516	22.031	61.70	120.9	...

Other Boundary Conditions

Boundary conditions can be expressed also by the relation between displacements and forces.


The shear in the beam is equal and opposite *a)* to the spring reaction or *b)* to the inertial force, so we can write, for a spring constant $k = \alpha EJ/L^3$

$$-EJ\phi'''(\beta L)q(t) + k\phi(\beta L)q(t) = 0$$

$$-EJ\phi'''(\beta L) + \alpha \frac{EJ}{L^3} \phi(\beta L) = 0$$

$$-L^3 \phi'''(\beta L) + \alpha \phi(\beta L) = 0$$

$$-(\beta L)^3 (-\mathcal{A} \cos \beta L + \dots) + \alpha \phi(\beta L) = 0$$



Other Boundary Conditions

Consider now an inertial force

$$M\ddot{u} = -\omega^2 M\phi(x)q(t)$$

(by $\ddot{q} = -\omega^2 q$), with $M = \gamma mL$ the equation of equilibrium is

$$-EJ\phi''''(\beta L)q(t) + M\phi(\beta L)\ddot{q}(t) = 0$$

$$-EJ\phi''''(\beta L)q(t) - \omega^2\gamma mL\phi(\beta L)q(t) = 0$$


$$-EJ\phi''''(\beta L) - \omega^2\gamma mL\phi(\beta L) = 0$$

by $\omega^2 = \beta^4 EJ/\gamma mL$


$$-EJ\phi''''(\beta L) - \beta^4 \frac{EJ}{\gamma mL} \gamma mL\phi(\beta L) = 0$$

$$-L^3\phi''''(\beta L) - (\beta L)^4\phi(\beta L) = 0$$

$$-(\beta L)^3(-A\cos\beta L + \dots) - (\beta L)^4\phi(\beta L) = 0$$



Other Boundary Conditions



Consider now an inertial force

$$M\ddot{u} = -\omega^2 M\phi(x)q(t)$$

(by $\ddot{q} = -\omega^2 q$), with $M = \gamma mL$ the equation of equilibrium is

$$-EJ\phi'''(\beta L)q(t) + M\phi(\beta L)\ddot{q}(t) = 0$$

$$-EJ\phi'''(\beta L)q(t) - \omega^2 \gamma mL\phi(\beta L)q(t) = 0$$

$$-EJ\phi'''(\beta L) - \omega^2 \gamma mL\phi(\beta L) = 0$$

by $\omega^2 = \beta^4 EJ/\gamma m$

$$-EJ\phi'''(\beta L) - \beta^4 \frac{EJ}{\gamma m} \gamma mL\phi(\beta L) = 0$$

$$-L^3 \phi'''(\beta L) - (\beta L)^4 \gamma \phi(\beta L) = 0$$

$$-(\beta L)^3 (-A \cos \beta L + \dots) - (\beta L)^4 \gamma \phi(\beta L) = 0$$

Similar considerations apply to equilibrium of bending moment and applied couple.

Mode Orthogonality

We will demonstrate mode orthogonality for a restricted set of boundary conditions, i.e., disregarding elastic supports and supported masses. In the beginning we have, for $n = r$,

$$[EJ(x)\phi_r''(x)]'' = \omega_r^2 m(x)\phi_r(x)$$

premultiplying both members by $\phi_s(x)$ and integrating over the length of the beam gives

$$\int_0^L \phi_s(x) [EJ(x)\phi_r''(x)]'' dx = \omega_r^2 \int_0^L \phi_s(x) m(x)\phi_r(x) dx$$

Mode Orthogonality, 2

The left member can be integrated by parts, two times, as in

$$\int_0^L \phi_s(x) [EJ(x)\phi_r''(x)]'' dx =$$
$$\left[\phi_s(x) [EJ(x)\phi_r''(x)]' \right]_0^L - \left[\phi_s'(x) EJ(x)\phi_r''(x) \right]_0^L +$$
$$\int_0^L \phi_s''(x) EJ(x)\phi_r''(x) dx$$

Mode Orthogonality, 2

The left member can be integrated by parts, two times, as in

$$\int_0^L \phi_s(x) [EJ(x)\phi_r''(x)]'' dx =$$
$$\left[\phi_s(x) [EJ(x)\phi_r''(x)]' \right]_0^L - \left[\phi_s'(x) EJ(x)\phi_r''(x) \right]_0^L +$$
$$\int_0^L \phi_s''(x) EJ(x)\phi_r''(x) dx$$

but the terms in brackets are always zero, the first being the product of end displacement by end shear, the second the product of end rotation by bending moment, and for fixed constraints or free end one of the two terms must be zero. So it is

$$\int_0^L \phi_s''(x) EJ(x)\phi_r''(x) dx = \omega_r^2 \int_0^L \phi_s(x) m(x)\phi_r(x) dx.$$

Mode Orthogonality, 3

We write the last equation exchanging the roles of r and s and subtract from the original,

$$\int_0^L \phi_s''(x) E J(x) \phi_r''(x) dx - \int_0^L \phi_r''(x) E J(x) \phi_s''(x) dx = \\ \omega_r^2 \int_0^L \phi_s(x) m(x) \phi_r(x) dx - \omega_s^2 \int_0^L \phi_r(x) m(x) \phi_s(x) dx.$$

This obviously can be simplified giving

$$(\omega_r^2 - \omega_s^2) \int_0^L \phi_r(x) m(x) \phi_s(x) dx = 0$$

implying that, for $\omega_r^2 \neq \omega_s^2$ the modes are orthogonal with respect to the mass distribution and the bending stiffness distribution.

Forced dynamic response

With $u(x, t) = \sum_1^{\infty} \phi_m(x) q_m(t)$, the equation of motion can be written

$$\sum_1^{\infty} m(x) \phi_m(x) \ddot{q}_m(t) + \sum_1^{\infty} [EJ(x) \phi_m''(x)]'' q_m(t) = p(x, t)$$

premultiplying by ϕ_n and integrating each sum and the loading term

$$\sum_1^{\infty} \int_0^L \phi_n(x) m(x) \phi_m(x) \ddot{q}_m(t) dx + \sum_1^{\infty} \int_0^L \phi_n(x) [EJ(x) \phi_m''(x)]'' q_m(t) dx = \int_0^L \phi_n(x) p(x, t) dx$$

By the orthogonality of the eigenfunctions this can be simplified to

$$m_n \ddot{q}_n(t) + k_n q_n(t) = p_n(t), \quad n = 1, 2, \dots, \infty$$

with

$$m_n = \int_0^L \phi_n m \phi_n dx, \quad k_n = \int_0^L \phi_n [EJ\phi_n''] dx,$$

$$\text{and} \quad p_n(t) = \int_0^L \phi_n p(x, t) dx.$$

For free ends and/or fixed supports, $k_n = \int_0^L \phi_n'' EJ \phi_n'' dx$.

Consider an effective earthquake load, $p(x, t) = m(x)\ddot{u}_g(t)$,
with

$$\mathcal{L}_n = \int_0^L \phi_n(x)m(x) dx, \quad \Gamma_n = \frac{\mathcal{L}_n}{m_n},$$

the modal equation of motion can be written (with an obvious generalisation)

$$\ddot{q}_n + 2\omega_n\zeta_n\dot{q}_n + \omega_n^2 q_n = -\Gamma_n\ddot{u}_g(t)$$

and the modal response can be written, also for the case of continuous structures, as the product of the modal participation factor and the deformation response,

$$q_n(t) = \Gamma_n D_n(t).$$

Modal contributions can be computed directly, e.g .

$$u_n(x, t) = \Gamma_n \phi_n(x) D_n(t),$$
$$M_n(x, t) = -\Gamma_n EJ(x) \phi_n''(x) D_n(t),$$

or can be computed from the equivalent static forces,

$$f_s(x, t) = [EJ(x)u(x, t)''']'' .$$

The modal contributions to equiv. static forces are

$$f_{sn}(x, t) = \Gamma_n [EJ(x)\phi_n(x)''']'' D_n(t),$$

that, because it is

$$[EJ(x)\phi''(x)]'' = \omega^2 m(x)\phi(x)$$


can be written in terms of the mass distribution and of the pseudo-acceleration response $A_n(t) = \omega_n^2 D_n(t)$

$$f_{sn}(x, t) = \Gamma_n m(x)\phi_n(x)\omega_n^2 D_n(t) = \Gamma_n m(x)\phi_n(x)A_n(t).$$

Earthquake response, 4

The effective load is proportional to the mass distribution, and we can do a modal mass decomposition in the same way that we had for *MDOF* systems,

$$m(x) = \sum r_n(x) = \sum \Gamma_n m(x) \phi_n(x)$$



Above, the modal mass decomposition $r_n = \Gamma_n m \phi_n$, for the first six modes of a uniform cantilever, in abscissa x/L .

EQ example, cantilever

For a cantilever, it is possible to derive explicitly some response quantities,

$$V(x), \quad V_b, \quad M(x), \quad M_b,$$

that is, the shear force and the base shear force, the bending moment and the base bending moment.

$$V_n^{\text{st}}(x) = \int_x^L r_n(s) ds, \quad V_b^{\text{st}} = \int_0^L r_n(s) ds = \Gamma_n \mathcal{L}_n = M_n^*$$

$$M_n^{\text{st}}(x) = \int_x^L r_n(s)(s-x) ds, \quad M_b^{\text{st}} = \int_0^L s r_n(s) ds = M_n^* h_n^*$$

M_n^* is the *participating modal mass* and expresses the participation of the different modes to the base shear, it is $\sum M_n^* = \int_0^L m(x) dx$.

$M_n^* h_n^*$ expresses the modal participation to base moment, h_n^* is the height where the participating modal mass M_n^* must be placed so that its effects on the base are the same of the static modal forces effects, or M_n^* is the resultant of s.m.f. and h_n^* is the position of this resultant.

Starting with the definition of total mass and operating a chain of substitutions,

$$\begin{aligned}M_{\text{tot}} &= \int_0^L m(x) dx = \sum \int_0^L r_n(x) dx \\&= \sum \int_0^L \Gamma_n m(x) \phi_n(x) dx = \sum \Gamma_n \int_0^L m(x) \phi_n(x) dx \\&= \sum \Gamma_n \mathcal{L}_n = \sum M_n^*,\end{aligned}$$

we have demonstrated that the sum of the participating modal mass is equal to the total mass.

The demonstration that $M_{b,\text{tot}} = \sum M_n^* h_n^*$ is similar and is left as an exercise.

EQ example, cantilever, 3

For the first 6 modes of a uniform cantilever,

n	\mathcal{L}_n	m_n	Γ_n	$V_{b,n}$	h_n	$M_{b,n}$
1	0.391496	0.250	1.565984	0.613076	0.726477	0.445386
2	-0.216968	0.250	-0.867872	0.188300	0.209171	0.039387
3	0.127213	0.250	0.508851	0.064732	0.127410	0.008248
4	-0.090949	0.250	-0.363796	0.033087	0.090943	0.003009
5	0.070735	0.250	0.282942	0.020014	0.070736	0.001416
6	-0.057875	0.250	-0.231498	0.013398	0.057875	0.000775
7	0.048971	0.250	0.195883	0.009593	0.048971	0.000470
8	-0.042441	0.250	-0.169765	0.007205	0.042442	0.000306

The convergence for M_b is faster than for V_b , because the latter is proportional to a higher derivative of displacements.